



5043 Farlin Ave.  
St. Louis, MO 63115



**ROTUNDA**

**MODEL: 331-9425**

**20 Amp / 25 Amp Peak Output Bench Charger / Power Supply for Standard Automotive, Deep-Cycle, AGM and Gel Cell batteries**



**Specifications:**

Model Number	9425
DC Output	20 Amps
DC Leads	6 ½' 10 AWG
Clamp Rating	300A
Limited Warranty	One Year
Shipping Dimensions	13.6"x13.6"x11.1"
Weight	21 LBS
AC Cord / Voltage	6' 18-3 / 120VAC 60 Hz
Battery Types	12 Volt Flooded, AGM, and Gel Cell batteries - including Spiral Cell, Orbital, or Optima batteries
Display	3 LED display indicating charge status

**Features:**

- **Electrical Stability System (ESS™)** technology turns 9425 into a stable power supply for extended service procedures or re-flashes. Nominal 13.7V DC Output
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Charges all types of 12 volt batteries.
- Designed for AGM, Gel Cell, Sealed, and Standard Flooded batteries including Spiral Cell, Orbital, or Optima batteries
- Dead Battery Override Control
- Made in USA

© 2016 Associated Equipment Corporation. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Product shipped may differ from photo(s) shown.