

NEW



LINCOLN

ROTUNDA



ALUSPOT

ALUMINUM REPAIR STATION
DF-900DX

Most complete aluminum panel repair station on the market

Everything you need to repair dents and creases from start to finish

Designed for ease of use with the technician in mind

Time saving innovations increase productivity and profitability



ALUSPOT DELUXE

ALUMINUM REPAIR STATION

Since 2006, the Aluspot has provided elite shops the tools needed to repair aluminum panels on exotic vehicles all over the world. The five simple steps for aluminum repair are included in the NEW all-in-one Aluspot Deluxe system: expose the bare aluminum by removing paint and oxidation, apply the proper heat range to the repair area, weld stud pins, pull the dent, and shape the dent. Unique features to this system include a ground located on the gun to eliminate the need for extra ground spots and additional blending, quick connect and disconnect stud fingers, and complete tool isolation to ensure protection against outside contaminants.

1-800-ROTUNDA www.OneRotunda.com

ALUMINUM REPAIR STATION

DF-900DX



LINCOLN

ROTUNDA



ALUSPOT

ALUMINUM REPAIR STATION



Die-cut Foam Inserts

Keep tools organized and accounted for. Drawers and cabinet can be locked.



Ground on Gun

Saves time, fewer spots to blend when finishing and painting.



Quick Pull Fingers

Easy on and off saves valuable time for each stud.



Total Isolation

Enclosed lockable drawers with keys and dust cover.



Ford Approved

Dent extraction system for the aluminum bodied 2015 F-150.

Aluspot Deluxe Includes:

- **Coating Removal**
*Inline pneumatic paint remover
 Fiber grind disc
 Stainless-steel shoe handle brush
 Stainless-steel tooth brush*
- **Heat Application**
*Digital set temperature heat gun
 Infrared temperature gauge*
- **Attach Stud Pins**
Capacitor discharge welder utilizing a self-contained, weld gun with ground Alu-Magnesium & Alu-Silicon stud pins (M4x25mm)
- **Dent Pulling**
*Hand T-puller
 Squeeze puller
 Lever puller
 Bridge puller
 Quick pull fingers*
- **Panel Shaping**
*Body file + 350mm blade
 Pick/finishing hammer
 Curved pein/finishing hammer
 Reverse-curve hammer
 22mm soft face hammer
 35mm dead blow hammer
 Bolster-head nylon chisel
 Round-head nylon chisel
 Double-end nylon dolly
 Utility dolly
 Double-end dolly
 Thin-toe dolly
 Heel dolly
 Curved dolly*
- **Isolation**
*Lockable drawers (3) + cabinet
 Dust cover*

Technical Specifications:

Capacitor Welder	
Hz:	50/60
Phase:	Single
Volts:	110-240V
Amp:	16
Ground:	Dual tipped, on gun
Dimensions	
Weight:	240 lbs
Length:	19.5"
Width:	26.5"
Height:	42"