

High Performance Platform

PFM X9 Base Model Shown

The PFM X9 combines our best existing technologies, like patented PFM one button computerized compensation system and 4 wheel-4 axis fully adjustable trolley, and marries them with a sporty new X-Frame lathe chassis, gib-less low maintenance gearbox, powerful high torque drivetrain, and super bright 6 LED light to give you a clear path to higher profits! X9's are digitally expandable to optional G2X and GYR systems.

WITH PRO-CUT, YOU CAN...

FIT ON EVERY VEHICLE. We have the adapters that will connect you to almost any vehicle on the road today and the power to turn stiff all-wheel drive and truck axles. And our simple setup is the same from sub compact to dual wheel trucks.

MATCHED ROTORS AS A NEW REVENUE SOURCE. Tires need to be balanced, wheels need to be aligned, and rotors need to be matched! Adding rotor matching to your service offerings adds a new revenue source.

SERVICE ANY VEHICLE ON ANY LIFT IN 6-8 MINUTES. Two post, four post, drive-on, or even no lift....it doesn't matter! *Pro-Cut's* fully adjustable trolley allows you to roll up and mount your *Pro-Cut* lathe with confidence.

FREE ON-SITE DEMO. GIVE US A CALL. Still not convinced? Call 1-800-543-6618 to set up a free on-site demo! Get hands on with the *Pro-Cut* X9 Rotor Matching System with no obligations.







*GIB-LESS 60 DEGREE GEAR BOX



**6 LED ON-BOARD WORK LIGHT

STANDARD FEATURES

BENEFIT

Includes BrakeSaver Point of Sale Marketing material	Provides exceptional Return on Investment (ROI); 4-6 months is common in busier shops!
Patented one touch Lateral Run Out (LRO) compensation	Press one button and the latest PFM lathes compensate in less than 20 seconds!
DRO "Live" digital computer display	Displays actual live LRO of machine & tracks # of compensations and duration.
Custom Calibrated Rate Sensor	Locks lathe in at .001" or less LRO every time you compensate for factory perfect cuts.
Cross Platform Compatible Computer & wiring harness	Allows use of plug & play G2X measuring Cutting Head & full GYR Technology Package.
4 Wheel, 4 Axis, Adjustable Trolley	Working Range of 21"to 43" allows the use on any lift or no lift!
2 YR parts & labor Warranty, 3 YR body warranty	Match Rotors day in and day out with peace of mind.(maintenance & abuse not covered).
*Gib-Less 60 degree Gear Box ·····	Maximum rigidity with low maintenance; Stays in tune for thousands of cuts!
**6 LED on-board work light ·····	Improves technician safety and efficiency in dark wheel wells.

PFM X9 SPECIFICATIONS -

SPEED LOCK CUTTING HEAD (Standard)		PRECISION-MATCH CUTTING HEAD (Optional)		MACHINE	
Maximum Rotor Thickness	1.75"	Maximum Rotor Thickness	2.00"	Spindle Speed	118 RPM
Minimum Rotor Thickness	0.2"	Minimum Rotor Thickness	0.2"	Carriage Speed	0.005" / rev.
Maximum Rotor Diameter	16.99"	Maximum Rotor Diameter	18.84" W/ 50-1492	Motor	1.00 HP
Maximum Friction Face	3.3"	Maximum Friction Face	3.90"	Shipping Weight	200 lbs.
Maximum Depth of Cut	0.015" / Side	Maximum Depth of Cut	0.020" / Side	Electrical Supply	120v / 1ph / 60hz
Weight	7.68 lbs	Weight	9.38 lbs	Feed Distance	6.95" (7.44"Opt.)

* Pro-Cut's PFM lathes are the first choice of the brake service industry. We have been approved by virtually every auto manufacturer and are considered essential equipment by most OEM's.

 $THIS\ SYSTEM\ IS\ SUBJECT\ TO\ ONE\ OR\ MORE\ OF\ U.S.\ PATENTS:\ 6,050,160\ /\ 6,101,911\ /\ 6,216,571\ /\ 6,327,947\ /\ 6,330,847\ /\ 6,474,203\ /\ 6,477,928\ /\ 6,895,851\ /\ 5,974,878\ /\ 7,607,377\ /\ 6,327,947\ /\ 6,327,947\ /\ 6,327,947\ /\ 6,327,947\ /\ 6,474,203\ /\ 6,477,928\ /\ 6,895,851\ /\ 5,974,878\ /\ 7,607,377\ /\ 6,216,217,217\ /\ 6,216,216,217\ /\ 6,216,217\ /\ 6,216,217\ /\ 6,216,217\ /\ 6,216,217\$





