

WORKHORSE OF THE INDUSTRY



Flex Vehicle Positioning

New photo eye vehicle sensing makes entering the wash bay smoother and easier ... no more treadle!

Tri-Color Detergent Applicator

New high-flow nozzle design for even, uniform vehicle coverage that looks great!

Onboard High-Pressure Turbo Wash

Blasts away grime in hard-toclean areas like wheels and rocker panels.

The SoftGloss MAXX has proven its success in the car wash industry. A combination of FoamBrite wash material and technological advancements will push customer satisfaction and revenue potential to the MAXX with this system. With 14 colors of FoamBrite wash material and an unlimited choice of colors for the body panels to choose from, you can design your machine to fit almost any color scheme imaginable.



- High-pressure combination wash option with rotating rocker blaster
- SoftGloss frame is made from aircraft-grade aluminum
- · Can accommodate duallies
- ColorWave compatible for increased customer experience and higher ticket value

- Onboard tire chemical applicator
- · Packaged with RainShield protectant
- · Higher throughput with five brushes
- Five brushes allow for required cleaning "touch time" with less time in-bay

SOFTGLOSS MAXX

Ryko Solutions







Overview of Additional Features

Rain Shield Protectant – Provides a profit generating opportunity to protect vehicle and glass surfaces against corrosives, oxidation and damaging UV rays. Also improves visibility, enhances color and shine and provides a water repellant coating.

Rotary Wheel Blaster – The zero degree turbo nozzles deliver an ultimate cleaning which provides an additional upsell opportunity.

On-Board Dry – Two powerful oscillating 10 HP fans provide a quick, satisfying drying result for any vehicle and a revenue generating feature for the wash owner.

Specifications

Electrical (basic)

Maximum Vehicle Height Maximum Vehicle Width (body) Water (min) Air (min)

95" 40 PSI @ 40 GPM, 1" 100 PSI @ 3 CFM, 3/8"

208/230V AC, 60 HZ, 3 Phase, And 120V AC, 60 HZ, 1 Phase

OR 460V AC, 60 HZ, 3 Phase, And 120V AC, 60 HZ, 1 Phase

Note: Equipment dimension specifications do not take into consideration any obstructions or unusual wash bay configurations, etc. Ryko Solutions, Inc., reserves the right to revise designs, add or delete features and change specifications at any time without notice or obligation.

Contact your Field Service Engineer or Rotunda Area Sales Manager





